

# 22-inch Full HD 1080p Optical Touch Display

## Intuitive Multi-Touch Design for Convenience and Better Working Efficiency

View  
See th



The 22" (21.5" viewable) ViewSonic® TD2220-2 is a multi-touch Full HD LED backlit monitor with 1920x1080 resolution, integrated speakers, DVI & VGA inputs and VESA mountable design. It has 20,000,000:1 MEGA Dynamic Contrast Ratio for sharp crisp images, and Eco-mode for up to 40%\* energy saving in the new 22" (21.5" viewable) offering. Perfect for both commercial and consumer applications. TD2220-2 supports the USB HID Touch driver and is compatible with Windows® 8. The TD2220-2 is the ideal solution for your multitouch monitor needs.

### Multi-touch Screen with 8H Surface Hardness

Simply touch, drag, resize and manipulate, photos, documents or web pages, just like on touch screen devices! 8H scratch resistant surface hardness ensures a consistent high quality touch experience and durability.

### Full HD 1080p Display with 1920x1080 Resolution

The 22" (21.5" viewable) Full HD monitor supports imaging intensive commercial applications such as image editing and entertainment. 20,000,000:1 MEGA Dynamic Contrast Ratio provides a high level of detail.

### Full HD 1080p for superlative pixel performance

The TD2220 features a Full HD 1920 x 1080p resolution for unbelievable pixel-by-pixel imaging. You'll experience the most amazing clarity and detail whether it be for working, gaming, or entertainment in multimedia entertainments. A 16:9 widescreen ratio minimizes eye fatigue even after hours of use. Perfectly compatible with multi-window viewing without toggling.

### OptiSync digital/analog inputs expand your connectivity

The TD2220-2 supports Windows® 8 touch function and boasts USB HID (Human Interface Device) touch and-play. The TD2220-2 can be connected through USB for instant two-point touch operation, experiencing easy navigation through intuitive touch operation. Two USB ports for additional peripherals and electronic devices. Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for compatibility and configuration flexibility.

### ENERGY STAR® and EPEAT Silver certified

The TD2220-2 is environmentally sound with Energy-saving LED backlight and Eco-mode for up to 40%\* in your energy cost comparing to a regular 22" monitor.

## Technical Specifications

<b>LCD</b>	<b>Type</b>	21.5" Wide
	<b>Display Area</b>	21.5 inch
	<b>Optimum Resolution</b>	1920x1080
	<b>Contrast Ratio</b>	1,000:1 (typical), 20,000,000 : 1 (DCR)
	<b>Brightness</b>	200 cd/m <sup>2</sup> (typ)
	<b>Viewing Angles</b>	170° / 160° (typ.)
	<b>Response Time</b>	5ms
	<b>Panel Surface</b>	8H Hardness
	<b>Light Source</b>	40,000 Hrs (Min.)
	<b>Video Input</b>	<b>Analog</b>
<b>Digital</b>		DVI-D (TMDS, 100Ω)
<b>Frequency</b>		Fh: 24-83KHz; Fv: 50-76Hz
<b>Sync</b>		Separate Sync / Composite Sync / SOG
<b>Compatibility</b>	<b>PC</b>	VGA up to 1920 x 1080
	<b>Mac</b>	MAC up to 1920 x 1080 (Touch function)
<b>Connector</b>	<b>Analog</b>	D-sub *1

	<b>Digital</b>	DVI *1
	<b>USB</b>	Up Stream: Type B *1 Down Stream: Type A *2
	<b>Power</b>	Internal Power Board, 3-pin Plug (CEE22)
<b>Power</b>	<b>Voltage</b>	AC 100–240V (universal), 50 / 60Hz
	<b>Consumption</b>	(ECO Mode)Standard: 26W; Optimize: 2
<b>Operating Conditions</b>	<b>Temperature</b>	0° ~ 40° C / 32° ~ 104° F
	<b>Humidity</b>	20%-90% (non-condensing)
<b>Dimensions</b>	<b>Physical</b>	511mm (width) x 365mm (height) x 240mm
<b>Weight</b>	<b>Net</b>	4.9 kg
<b>Regulations</b>		CE, CB, BSMI, PSB, SASO, C-tick, e-star FCC-B (including ICES003), UL CoC, Me GOST-R/Hygienic, UkrSEPRO, Erp, CC Energy, ENERGY STAR®, EPEAT Silver SVHC list
<b>Wall Mount</b>		100mm x 100mm
<b>Package Contents</b>		TD2220-2 display, power cable, AC/DC cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD (available in some